

MODEL:		TYPE
PROJECT:		
PREPARED BY:	DATE:	

SERIES SPECIFICATIONS

12/2 Landscape Cable, Low Voltage, Direct Burial, 500 Ft.

UV Resistant for outdoor use

Suitable for accent outdoor lighting, including landscape and securi-

ty not exceeding 150V

Rated for underground burial use

Duplex flat construction for easy sepeartion of conductors for instal-

lation





CONSTRUCTION

Color Data Rate Temperature Rating

Black 150V From -20°C to 60°C maximum

Conductor Material Shield Coverage Shield Material

Copper N/A From -20°C to 60°C maximum

Jacket Flame Rate Jacket Type

PVC

ELECTRICAL SPECIFICATIONS

AWG Conductors Jacket Nom. Diameter

12 2 N/A

Jacket Nom. Thickness Wire Construction Conductor Construction

0.46 - 0.52 Stranded Flat 65 x 0.254

Resistance

N/A

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION





MODEL:		TYPE
PROJECT:		
PREPARED BY:	DATE:	

CERTIFICATIONS/WARRANTY

Listing
UL listed Listed

Warranty

Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

ORDERING INFORMATION

Part Number: LV 12/2 - 500

Box Qty : 500 Ft. Weight (Lbs) : 0.0595

Carton Qty.: 500 Ft. IMS Code: 0252-8799

