

CONTRACTOR:		
PROJECT:	DATE:	
PREPARED BY:	MODEL: MBL-HM-FDR	

SPECIFICATION & FEATURES

Mobile Home Feeder Cable is used to provide power from the electrical disconnect to the distribution panel board in mobile home applications, suitable for direct burial in earth at conductor temperatures not to exceed 90°C.

- Sunlight resistant, moisture resistant and flame retardant insulation.
- Insulation is heavy metal free in compliance with RoHS wet and dry locations.





CERTIFICATIONS/WARRANTY

Listing: UL44/UL854 **RoHS:** RoHS Compliant

Warranty

Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

CONSTRUCTION

Max. Rating 600V	Temperature Rating 90°C	Insulation Material POLYETHYLENE (XLP)	Color BLK/BLK/BLK/GRN
Length	Conductor Material	Number Of Conductors	Package Type
1000FT	8000 Series Aluminum	4	Reel





CONTRACTOR:	
PROJECT:	DATE:
PREPARED BY:	MODEL:

ORDERING INFORMATION

Part Code	IMS Code	Conductor Size	Strands	Outside Diameter
MBL-HM-FDR-2-2-4-6-A	0609-1701	2-2-4-6	7/7/7/7	0.944 IN
MBL-HM-FDR-2-2-4-A	0609-1704	2-2-2-4	7/7/7/7	0.944 IN
MBL-HM-FDR-2/0-2/0-1-4-A	0609-1707	2/0-2/0-1-4	18/18/18/7	1.301 IN
MBL-HM-FDR-4/0-4/0-2/0-4-A	0609-1710	4/0-4/0-2/0-4	19/19/18/7	1.54 IN
MBL-HM-FDR-4/0-4/0-4/0-2/0-A	0609-1725	4/0-4/0-4/0-2/0	19/19/19/18	1.54 IN