

MODEL:		TYPE
PROJECT:		
PREPARED BY:	DATE:	

SERIES SPECIFICATIONS

20A 120/277V Single Pole Toggle Switch, Push-In/Side Wire

Impact resistant, thermoplastic toggle & frame for increased durabil-

ity

Faster installation with push-in and side wiring options

Triple combination screws for fast wiring installation (Slotted, Phillips,

& Robertson)

Thick plated steel strap withstands abuse & corrosion





CONSTRUCTION

Color

Light Almond

Strap Material

Galvanized Steel

Grade

Commercial Grade

Environmental Rating

Flammability UL94, V2 Rating

Device Type Toggle

Operation Temperature

From -40°C (without impact) to 75°C Maximum continuous

ELECTRICAL SPECIFICATIONS

Amperage

20 Ampere

Termination 1

Push-In #14 AWG Cu Solid wire

only

Voltage 120/277 V AC

Termination 2

Side Wired, #12 AWG - #14

AWG Cu Solid or Stranded

wire

Poles

Grounding Capable

Grounding

CERTIFICATIONS/WARRANTY

Listing

UL Listed Listed

Warranty

Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION





MODEL:		TYPE
PROJECT:		
PREPARED BY :	DATE:	

ORDERING INFORMATION

Part Number: CSB120-LA

Box Qty: 10 Weight (Lbs): 0.1560

Carton Qty.: 100 IMS Code: 0279-6909

