

#### SERIES SPECIFICATIONS

30A 125/250V, 3 Pole/3-Wire Flush Mount Dryer Receptacle All mounting hardware included Flush mount receptacles fit in one or two gang enclosures Available in white or black Receptacle for use with copper wire





#### CONSTRUCTION

Color White

Strap Material Steel/Zinc Plated

NEMA Configuration 1030-R

### **ELECTRICAL SPECIFICATIONS**

Amperage 30 Ampere

Termination 1 #4 to #10 AWG Cu conductors

Wires 3 Grade Residential

MODEL :

PROJECT :

**PREPARED BY :** 

Environmental Rating Flammability UL94, V2 Rating Device Type Receptacle

DATE :

Operation Temperature N/A

125/250 V AC

Voltage

Termination 2

Poles 3

Grounding Capable Non-Grounding

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION





MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

# CERTIFICATIONS/WARRANTY

Listing UL listed Listed

Warranty

Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

## ORDERING INFORMATION

Part Number: FMD1030R-WH

Box Qty:10

Carton Qty.: 40

Weight (Lbs) : 0.331

IMS Code : 0276-8262

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION

