



MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

SERIES SPECIFICATIONS

20A 125V Duplex Receptacle, Back/Side Wired, Isolated Ground
 Automatic grounding clip provides safe ground continuity between strap and metal enclosure
 Side located grounding screw backed out and ready to wire
 One-piece, triple-wipe brass line contacts for minimum heat rise, maximum plug retention
 Break-off tabs for easy two-circuit conversion



CONSTRUCTION

Color
Orange

Grade
Isolated Ground

Device Type
Duplex Receptacle

Strap Material
Steel

Environmental Rating
Flammability UL94, V2 Rating

Operation Temperature
From -40°C (without impact)
to 75°C Maximum continuous

NEMA Configuration
5-20R

ELECTRICAL SPECIFICATIONS

Amperage
20 Ampere

Voltage
125 V AC

Poles
2

Termination 1
Back Wired #10 - #14 wire

Termination 2
Side Wired, #12 AWG - #14
AWG Cu Solid or Stranded
wire

Grounding Capable
Grounding

Wires
3

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION



404 NW ENTERPRISE DR. PORT ST. LUCIE, FL 34986 | 772.408.5213 | WWW.RPP-USA.COM



MODEL :		TYPE
PROJECT :		
PREPARED BY :	DATE :	

CERTIFICATIONS/WARRANTY

Listing
UL listed Listed

Warranty
Guaranteed for one year from the purchase date of the product, against mechanical defects in manufacturing.

ORDERING INFORMATION

Part Number: IGR20-OR

Box Qty : 10

Weight (Lbs) : 0.181

Carton Qty. : 100

IMS Code : 0288-1716

APPLICATION AND PERFORMANCE SPECIFICATION INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTIFICATION

